

Questionnaire for Voltage Detectors

To prepare an offer, please fill in this questionnaire as detailed as possible and return by fax, post or e-mail.

Fax +49 89 / 43 60 473
 Post ARCUS ELEKTROTECHNIK Alois Schiffmann GmbH • Truderinger Straße 199 • 81673 Munich/Germany
 E-mail info@arcus-schiffmann.com

Contact Information

Last name	First name
Company	Department
Street, number	Zip code, town
Phone	Fax
E-mail	Web

Voltage Detectors

Application	☐	Substations	  
	☐	Overhead lines	
	☐	Railway energy installations	
	☐	Traction current lines (off rail track)	
	☐	Railway contact wire	
	☐		
Earthing / Net arrangement	☐	star point isolated neutral 3-phase system	  
	☐	single-side isolated neutral 1-phase system	
	☐	centre-isolated neutral 1-phase system	
	☐		
Nominal voltage Un	 kV		

Questionnaire for Voltage Detectors (continued)

Frequency f	☐	16.7 Hz		
	☐	50 Hz		
	☐	60 Hz		
Voltage detector	☐	ARCUSDETECT M (3-36 kV)	☐	Outdoor use
	☐	ARCUSDETECT H (36-420 kV)	☐	Outdoor use
	☐	ARCUSDISTANT (110-380 kV)	☐	Outdoor use
			☐	Indoor use
			☐	Indoor use
Total length LG	approx. mm			
Transport length LT	approx. mm			
Contact electrode	☐	Threaded electrode		
	☐	Fork contacts (accessories)		
	☐	Hook contact (only for railway contact wires)		
Reference detector model				
Special requirements				
Special requirements Accessories				

Others

Required quantity	Required delivery time
Language of documentation	Others

Date	Signature
------------	-----------------